


according to 1907/2006/EC, Article 31

Printing date 15.09.2023

Version number 2 (replaces version 1)

Revision: 15.09.2023



according to 1907/2006/EC, Article 31

Printing date 15.09.2023

Revision: 15.09.2023

Trade name: AllorA 2K Klarlack Härter normal

(Contd. of page 1) n-Butyl acetate 2-Methoxy-1-methylethyl acetate · Hazard statements Flammable liquid and vapour. H226 Harmful if inhaled. H332 May cause an allergic skin reaction. H317 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. · Additional information: EUH066 Repeated exposure may cause skin dryness or cracking. EUH204 Contains isocyanates. May produce an allergic reaction. Restricted to professional users. · 2.3 Other hazards · Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

# SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

| CAS: 28182-81-2   | Hexamethylene diisocyanate, oligomers   | 50-100% |
|---|---|---------|
| NLP: 500-060-2<br>Reg.nr.: 01-2119485796-17                     | Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335, EUH204   |         |
| CAS: 123-86-4<br>EINECS: 204-658-1<br>Reg.nr.: 01-2119485493-29 | n-Butyl acetate<br>Flam. Liq. 3, H226; () STOT SE 3, H336, EUH066   | 10-25%  |
| CAS: 108-65-6<br>EINECS: 203-603-9<br>Reg.nr.: 01-2119475791-29 | 2-Methoxy-1-methylethyl acetate<br>Flam. Liq. 3, H226;  STOT SE 3, H336   | 10-25%  |
| CAS: 112-07-2<br>EINECS: 203-933-3<br>Reg.nr.: 01-2119475112-47 | 2-Butoxyethyl acetate<br>Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332   | 5-<10%  |
| EINECS: 212-485-8   | <ul> <li>hexamethylene-di-isocyanate</li> <li>Acute Tox. 2, H330;  Resp. Sens. 1, H334;  Acute Tox. 4, H302;</li> <li>Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204</li> <li>Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 %</li> <li>Skin Sens. 1; H317: C ≥ 0.5 %</li> </ul> | <0.1%   |

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Printing date 15.09.2023

#### Version number 2 (replaces version 1)

Revision: 15.09.2023

#### Trade name: AllorA 2K Klarlack Härter normal

(Contd. of page 2)

## **SECTION 4: First aid measures**

#### · 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- $\cdot$  5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released: Nitrogen oxides (NOx) Carbon monoxide (CO) Hydrogen cyanide (HCN)

- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

## **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Contain and collect spillages with non-combustible absorbent materials (e.g. sand, earth, diatomaceous earth) and place in a suitable container.

Decontaminate immediately with suitable mixture (flammable):

- as such usable (inflammatory!):

| water                            | 45 Vol.% |
|----------------------------------|----------|
| ethanol or isopropanol           | 50 Vol.% |
| ammonia solution (Density= 0.88) | 5 Vol.%  |
| - alternatively (non-flammable): |          |
| sodium carbonate                 | 5 Vol.%  |
| water                            | 95 Vol.% |

Add the same decontaminant to any residues and allow to stand for several days in an non-sealed container until no further reaction occurs. Once this stage is reached, close the container and dispose of in accordance with the waste regulations (see Section 13).

(Contd. on page 4)

GB

according to 1907/2006/EC, Article 31

Printing date 15.09.2023

## Version number 2 (replaces version 1)

Revision: 15.09.2023

(Contd. of page 3)

Trade name: AllorA 2K Klarlack Härter normal

#### · 6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Persons with a history of asthma, allergies or chronic or recurrent respiratory diseases should only be employed in processes in which this product is used under appropriate medical supervision.

Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

### · 7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility:

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis. Store away from foodstuffs.

- Further information about storage conditions: Keep container tightly sealed. Store separately from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohol and water.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

#### · 8.1 Control parameters

| Ingree | dients with limit values that require monitoring at the workplace:               |                 |
|--------|--|-----------------|
| 28182  | -81-2 Hexamethylene diisocyanate, oligomers                                      |                 |
| EBW    | Short-term value: 0.5 mg/m³<br>exposition evaluation valu TRGS 430 (EBW)         |                 |
| 123-8  | 6-4 n-Butyl acetate  |                 |
| WEL    | Short-term value: 966 mg/m³, 200 ppm<br>Long-term value: 724 mg/m³, 150 ppm      |                 |
| 108-6  | 5-6 2-Methoxy-1-methylethyl acetate  |                 |
| WEL    | Short-term value: 548 mg/m³, 100 ppm<br>Long-term value: 274 mg/m³, 50 ppm<br>Sk |                 |
| 112-0  | 7-2 2-Butoxyethyl acetate  |                 |
| WEL    | Short-term value: 332 mg/m³, 50 ppm<br>Long-term value: 133 mg/m³, 20 ppm<br>Sk  |                 |
| 822-0  | 6-0 hexamethylene-di-isocyanate  |                 |
| WEL    | Short-term value: 0.07 mg/m³<br>Long-term value: 0.02 mg/m³<br>Sen; as -NCO      |                 |
|        |  | (Contd. on page |

according to 1907/2006/EC, Article 31

Printing date 15.09.2023

#### Version number 2 (replaces version 1)

Revision: 15.09.2023

Trade name: AllorA 2K Klarlack Härter normal

|   | (Contd. of page 4) |
|---|--------------------|
| · Ingredients with biological limit values: |                    |
|   |                    |

## 822-06-0 hexamethylene-di-isocyanate

#### BMGV 1 µmol creatinine/mol Medium: urine

Sampling time: At the end of the period od exposure

Parameter: isocyanate-derived diamine

• Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.
- · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### • Eye/face protection



Tightly sealed goggles

| 9.1 Information on basic physical a | and chemical properties            |
|-------------------------------------|------------------------------------|
| General Information                 |                                    |
| Physical state                      | Fluid                              |
| Colour:                             | According to product specification |
| Odour:                              | Characteristic                     |
| Odour threshold:                    | Not determined.                    |

- GB

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.09.2023

Version number 2 (replaces version 1)

Revision: 15.09.2023

Trade name: AllorA 2K Klarlack Härter normal

|   | (Contd. of page   |
|---|---|
| Melting point/freezing point:   | Undetermined.   |
| Boiling point or initial boiling point and boiling  |   |
| range   | 124-128 °C (123-86-4 n-Butyl acetate)   |
| Flammability  | Flammable.  |
| Lower and upper explosion limit   |   |
| Lower:  | 1.2 Vol %   |
| Upper:  | 10.8 Vol %  |
| Flash point:  | 27 °C (DIN 53213)   |
| Auto-ignition temperature:  | 280 °C (DIN 51794)  |
| Decomposition temperature:  | Not determined.   |
| pH  | Not determined.   |
| Viscosity:  |   |
| Kinematic viscosity at 20 °C  | 10-15 s (DIN 53211/4)   |
| Dynamic:  | Not determined.   |
| Solubility  |   |
| water:  | Not miscible or difficult to mix.   |
| Partition coefficient n-octanol/water (log value)   | Not determined.   |
| Vapour pressure at 20 °C:   | 10.7 hPa  |
| Vapour pressure at 50 °C:   | 55 hPa  |
| Density and/or relative density   |   |
| Density at 20 °C:   | 1.036 g/cm³ (DIN 53217)   |
| Relative density  | Not determined.   |
| Vapour density  | Not determined.   |
| • •   |   |
| 9.2 Other information   |   |
| Appearance:   |   |
| Form:   | Fluid   |
| Important information on protection of health and   | d   |
| environment, and on safety.   |   |
| Ignition temperature:   | Product is not selfigniting.  |
| Explosive properties:   | Product is not explosive. However, formation of explosive   |
|   | air/vapour mixtures are possible.   |
| Solvent content:  |   |
| VOC (EC)  | 45.99 %   |
| Solids content (weight-%):  | 54.0.00   |
|   | 54.0 %  |
| Change in condition   | 54.0 %  |
|   | Not determined.   |
| Evaporation rate  | Not determined.   |
| Evaporation rate<br>Information with regard to physical hazard classes  | Not determined.   |
| Evaporation rate<br>Information with regard to physical hazard classes<br>Explosives  | Not determined.<br>s<br>Void  |
| Evaporation rate<br>Information with regard to physical hazard classes<br>Explosives<br>Flammable gases   | Not determined.<br>s<br>Void<br>Void  |
| Evaporation rate<br>Information with regard to physical hazard classes<br>Explosives<br>Flammable gases<br>Aerosols   | Not determined.<br>s<br>Void<br>Void<br>Void  |
| Evaporation rate<br>Information with regard to physical hazard classes<br>Explosives<br>Flammable gases<br>Aerosols<br>Oxidising gases  | Not determined.<br><b>s</b><br>Void<br>Void<br>Void<br>Void<br>Void   |
| Evaporation rate<br>Information with regard to physical hazard classes<br>Explosives<br>Flammable gases<br>Aerosols<br>Oxidising gases<br>Gases under pressure  | Not determined.<br><b>s</b><br>Void<br>Void<br>Void<br>Void<br>Void<br>Void<br>Void                                   |
| Evaporation rate<br>Information with regard to physical hazard classes<br>Explosives<br>Flammable gases<br>Aerosols<br>Oxidising gases<br>Gases under pressure<br>Flammable liquids   | Not determined.<br><b>s</b><br>Void<br>Void<br>Void<br>Void<br>Void<br>Void<br>Flammable liquid and vapour.           |
| Evaporation rate<br>Information with regard to physical hazard classes<br>Explosives<br>Flammable gases<br>Aerosols<br>Oxidising gases<br>Gases under pressure<br>Flammable liquids<br>Flammable solids   | Not determined.<br><b>s</b><br>Void<br>Void<br>Void<br>Void<br>Void<br>Void<br>Flammable liquid and vapour.<br>Void   |
| Evaporation rate<br>Information with regard to physical hazard classes<br>Explosives<br>Flammable gases<br>Aerosols<br>Oxidising gases<br>Gases under pressure<br>Flammable liquids<br>Flammable solids<br>Self-reactive substances and mixtures  | Not determined.  S Void Void Void Void Void Void Flammable liquid and vapour. Void Void Void                          |
| Evaporation rate<br>Information with regard to physical hazard classes<br>Explosives<br>Flammable gases<br>Aerosols<br>Oxidising gases<br>Gases under pressure<br>Flammable liquids<br>Flammable solids<br>Self-reactive substances and mixtures<br>Pyrophoric liquids  | Not determined.  S Void Void Void Void Void Void Flammable liquid and vapour. Void Void Void Void Void Void Void      |
| Evaporation rate<br>Information with regard to physical hazard classes<br>Explosives<br>Flammable gases<br>Aerosols<br>Oxidising gases<br>Gases under pressure<br>Flammable liquids<br>Flammable solids<br>Self-reactive substances and mixtures<br>Pyrophoric liquids<br>Pyrophoric solids   | Not determined.  S Void Void Void Void Void Flammable liquid and vapour. Void Void Void Void Void Void Void Void      |
| Evaporation rate<br>Information with regard to physical hazard classes<br>Explosives<br>Flammable gases<br>Aerosols<br>Oxidising gases<br>Gases under pressure<br>Flammable liquids<br>Flammable solids<br>Self-reactive substances and mixtures<br>Pyrophoric liquids<br>Pyrophoric solids<br>Self-heating substances and mixtures   | Not determined.  S Void Void Void Void Void Void Flammable liquid and vapour. Void Void Void Void Void Void Void      |
| Evaporation rate<br>Information with regard to physical hazard classes<br>Explosives<br>Flammable gases<br>Aerosols<br>Oxidising gases<br>Gases under pressure<br>Flammable liquids<br>Flammable solids<br>Self-reactive substances and mixtures<br>Pyrophoric liquids<br>Pyrophoric solids<br>Self-heating substances and mixtures<br>Substances and mixtures, which emit flammable  | Not determined.  S Void Void Void Void Void Flammable liquid and vapour. Void Void Void Void Void Void Void Void      |
| Evaporation rate<br>Information with regard to physical hazard classes<br>Explosives<br>Flammable gases<br>Aerosols<br>Oxidising gases<br>Gases under pressure<br>Flammable liquids<br>Flammable solids<br>Self-reactive substances and mixtures<br>Pyrophoric liquids<br>Pyrophoric solids<br>Self-heating substances and mixtures<br>Substances and mixtures, which emit flammable<br>gases in contact with water   | Not determined.  S Void Void Void Void Void Flammable liquid and vapour. Void Void Void Void Void Void Void Void      |
| Evaporation rate<br>Information with regard to physical hazard classes<br>Explosives<br>Flammable gases<br>Aerosols<br>Oxidising gases<br>Gases under pressure<br>Flammable liquids<br>Flammable solids<br>Self-reactive substances and mixtures<br>Pyrophoric liquids<br>Pyrophoric solids<br>Self-heating substances and mixtures<br>Substances and mixtures, which emit flammable<br>gases in contact with water   | Not determined.  S Void Void Void Void Void Void Flammable liquid and vapour. Void Void Void Void Void Void Void Void |
| Change in condition<br>Evaporation rate<br>Information with regard to physical hazard classes<br>Explosives<br>Flammable gases<br>Aerosols<br>Oxidising gases<br>Gases under pressure<br>Flammable liquids<br>Flammable solids<br>Self-reactive substances and mixtures<br>Pyrophoric liquids<br>Pyrophoric solids<br>Self-heating substances and mixtures<br>Substances and mixtures, which emit flammable<br>gases in contact with water<br>Oxidising liquids<br>Oxidising solids | Not determined.  S Void Void Void Void Void Void Flammable liquid and vapour. Void Void Void Void Void Void Void Void |
| Evaporation rate<br>Information with regard to physical hazard classes<br>Explosives<br>Flammable gases<br>Aerosols<br>Oxidising gases<br>Gases under pressure<br>Flammable liquids<br>Flammable solids<br>Self-reactive substances and mixtures<br>Pyrophoric liquids<br>Pyrophoric solids<br>Self-heating substances and mixtures<br>Substances and mixtures, which emit flammable<br>gases in contact with water<br>Oxidising liquids  | Not determined.  S Void Void Void Void Void Void Flammable liquid and vapour. Void Void Void Void Void Void Void Void |

according to 1907/2006/EC, Article 31

Printing date 15.09.2023

#### Version number 2 (replaces version 1)

Revision: 15.09.2023

(Contd. of page 6)

Trade name: AllorA 2K Klarlack Härter normal

|                         |      | (Conta, or page 6) |
|-------------------------|------|--------------------|
| · Corrosive to metals   | Void |                    |
| Desensitised explosives | Void |                    |

#### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Possible in traces. Nitrogen oxides Hydrogen chloride (HCI) Hydrogen cyanide (prussic acid) Carbon monoxide Nitrogen oxides (NOx)

#### **SECTION 11: Toxicological information**

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if inhaled.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

#### **SECTION 13: Disposal considerations**

- 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.09.2023

## Version number 2 (replaces version 1)

Revision: 15.09.2023

(Contd. of page 7)

Trade name: AllorA 2K Klarlack Härter normal

• Uncleaned packaging:
 • Recommendation: Disposal must be made according to official regulations.

| 14.1 UN number or ID number<br>ADR, IMDG, IATA    | UN1263  |
|---|---|
| 14.2 UN proper shipping name<br>ADR<br>IMDG, IATA | UN1263 PAINT RELATED MATERIAL<br>PAINT RELATED MATERIAL |
| 14.3 Transport hazard class(es)                   |   |
| ADR   |   |
|   |   |
| Class   | 3 (F1) Flammable liquids.                               |
| Label<br>IMDG, IATA                               | 3   |
|   |   |
| Class<br>Label                                    | 3 Flammable liquids.<br>3                               |
| 14.4 Packing group                                | 5   |
| ADR, IMDG, IATA                                   | III   |
| 14.5 Environmental hazards:<br>Marine pollutant:  | No  |
| 14.6 Special precautions for user                 | Warning: Flammable liquids.                             |
| Hazard identification number (Kemler code):       | 30  |
| EMS Number:<br>Stowage Category                   | F-E, <u>S-E</u><br>A                                    |
| 14.7 Maritime transport in bulk according to IM   |   |
| instruments                                       | Not applicable.   |
| Transport/Additional information:                 | •••   |
| ADR   |   |
| Limited quantities (LQ)                           | 5L  |
| Transport category                                | 3   |
| Tunnel restriction code                           | D/E   |
| IMDG  | -   |
| Limited quantities (LQ)                           | 5L  |

(Contd. on page 9)

according to 1907/2006/EC, Article 31

Printing date 15.09.2023

#### Version number 2 (replaces version 1)

Revision: 15.09.2023

#### Trade name: AllorA 2K Klarlack Härter normal

(Contd. of page 8)

GB

#### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations:

```
· Additional classification according to Decree on Hazardous Materials, Annex II:
```

Class | Share in %

| NK | 25-50 |
|----|-------|

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- May cause an allergic skin reaction. H317
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- May cause respiratory irritation. H335
- H336 May cause drowsiness or dizziness.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- EUH204 Contains isocyanates. May produce an allergic reaction.
- Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

#### Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

- VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids Category 3
- Acute Tox. 2: Acute toxicity Category 2 Acute Tox. 4: Acute toxicity Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

- Eye Irrit. 2: Serious eye damage/eye irritation Category 2
- Resp. Sens. 1: Respiratory sensitisation Category 1
- Skin Sens. 1: Skin sensitisation Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

• \* Data compared to the previous version altered.